

DIESEL HVO30

Property	Unit	Minimum	Maximum	Test method	
Cetane number	-	56,7	-	EN ISO 5165	
Density at 15 °C	kg/m ³	800,0	845,0	EN ISO 3675	
Sulfur content	mg/kg	-	10,0	EN ISO 20846	
Manganese content	mg/l	-	2,0	EN 16576	
Flash Point	°C	>55	-	EN ISO 22719	
Carbon residue on 10% distillation residue	% m/m	-	0,3	EN ISO 10370	
Ash content	% m/m	-	0,0	EN ISO 6245	
Water content	mg/kg	-	200	EN ISO 12937	
Copper strip corrosion (3 hrs. at 50 °C)	Rating	Class 1		EN ISO 2160	
	h	20	-	EN 15751	
Lubricity, corrected wear score diameter (wsd 1,4) at 60° C	µm	-	460	EN ISO 12156-1	
Viscosity at 40°C	mm ² /s	2,0	4,5	EN ISO 3104	
Fatty acid methyl ester (FAME) content	% v/v	-	0,0	EN ISO 14078	
Distillation	% (v/v) recovered at 250 °C	% v/v	-	<65	EN ISO 3405
	% (v/v) recovered at 350 °C	% v/v	85	-	
	95 % (v/v) recovered at	°C	-	360	
CFPP	Summer*	°C	-	-5	EN 116
	Intermediate**	°C	-	-11	
	Winter***	°C	-	-20	

* Summer: May 1st - October 15th

** Intermediate: October 16th - November 15th / March 1st - April 30th

*** Winter: November 16th - Februari 28th

Edition: 2020

Version: 2